

HIGH FREQUENCY SCREENS

FROM CONCEPTS TO REALITY



ENGINEERED FOR EFFICIENCY

DESIGNED TO YOUR SPECS

BUILT FOR DURABILITY

www.tcimfg.com - 815.379.2090



Various Configurations and Customizable Options Available

TCI High-Frequency Screens have the highest screen capacity in the industry for dry, fine material separation.





TCI high frequency screens, commonly referred to as "PEP screens", come in a variety of sizes, frequency levels and configurations. Fine material is best separated with high speed and a small stroke. They are available in single or double deck configurations, and are equipped with either electric or hydraulic vibration. The ratchet-type screen tensioning makes for easy screen panel changes

<u>Note</u>: Figures calculated on the use of slotted screens material to be screened contains overs to stimulate production and provide scouring.

- Assumes material weight 100 lbs per cubic foot
- This chart is to be used for estimation Purposes only. All application variables should be considered when evaluating tonnages

Basic Capacity Table			
	Dry		
Through Deck	Material		
Slotted Screen	6x12	6x18	6x24
3/8	240 TON	288	345
1/4	210 TON	252	302
3/16 (4M)	175 TON	210	252
1/8 (6M)	115 TON	138	165
3/32 (8M)	85 TON	102	122
5/64 (10M)	65 TON	78	93
1/16 (12M)	50 TON	60	73
3/64 (16M)	40 TON	48	58





TCI - HIGH FREQUENCY SCREENS





6x18 PSB Plant

- **Stationary or Skid-Mount**
- TCI High-Frequency Screens are engineered to provide the highest production capabilities in the market. Aggressive vibration (3600RPM) applied directly to screen media allows for higher capacity and more efficient sizing, compared with conventional screens
- Standard separations range from ½"to 20M
- Faster screen media changes with a tool-free ratchet system
- Designed to increase production by removing fines in both pre-screening and post-screening applications

Standard sizes include: 6x12, 6x18, & 6x24 Applications include:

Fractionated / Recycled Asphalt (FRAP/RAP), Chip sizing, Fines removal, Ag-lime, Manufactured sand





6x24 PTSC XL





THE TCI DIFFERENCE

- In-house engineering
- Custom design & fabrication
- Precision shopwelded and bolted
- Anything from standard enamel to custom paint formulations
- Rigorous product testing & fitting



From our humble beginning in 2000, TCI has grown significantly due to our high quality product line, our attention to detail, and our loyal and growing dealers and customer base. Our on-site facility has over 100,000 sq ft of manufacturing space. Our in-house engineering and CNC equipment allows us to efficiently and accurately custom design and build almost anything imaginable.



28524 1250 East Street PO Box 306, Walnut, IL 61376 815-379-2090 www.tcimfg.com

